

TECHNICAL DATA SHEET

Page 1 of 2

Product: UV-SPEEDOIL TOPCOAT

Number: 91880004-000, NATURAL



Description: Solvent and formaldehyde free UV-curing oil for roller application in the coating process of parquet. This product provides a decorative effect and protects the substrate from chemical impacts and dirt. The product is available in natural and standard white colour.

Application:

Preparation: Stir well before use.
Hardener: None
Thinner: Not required.
Viscosity: As delivered
Film Weight: Apply 4 - 6 g/m²
Mode: Apply in roller coater with a shore hardness of preferably 40 - 50 (Isobutylen/Isopren-Copolymer or EPDM-Prepolymer) or sponge roller.
UV-Curing: Cure with a mercury lamp with at least 80 W/cm² (5 m/min). The curing time depends on the type and number of lamps as well as on the line speed.

Substrate: The product is especially formulated as UV-Speedoil Topcoat to be applied on TREFFERT UV-Speedoil Basecoat.
Please consult our technical staff prior to other applications.

TECHNICAL DATA SHEET

Page 2 of 2

Product: UV-SPEEDOIL TOPCOAT

Number: 91880004-000, NATURAL



Storage:

Shelf life: 6 months.
Conditions: Protect from sunlight and frost.
To be stored at 5 - 35°C

Delivery:

Packaging: Available in 20 kg pails.
Delivery times: Please allow 10 working days of production plus transport.
Quantities: Except for trial orders, minimum order quantity is 600 kg per individual product.

Cleaning:

Refer to roller manufacturer's data, then consult our technical service department.

Precautions:

Avoid skin contact as skin irritation may occur.
Refer to Health and Safety Data Sheet.

Health & Safety:

Refer to Health and Safety Data Sheet.

22.01.04/Kg